

Technical Data Sheet



Product name : Recowool 42

Description : Carpet Underlay



Felt underlay has become sustainable. Using 80% wool new carpet off-cuts, we are able to achieve a high wool content in our underlay ensuring an underlay that has comfort, warmth and support for a good carpet.

Applications:	Felt underlay is recommended by carpet manufacturers to enhance the performance of the carpet.
Fibre composition:	Wool/polypropylene
Nominal weight:	1424g/m ² (+/- 5%), (42oz/yd ²)
Nominal thickness:	10.0mm
Roll width:	1.37m
Roll length:	11m
Standard roll area:	15.07m ²
Flame retardancy: BS4790:1987 (Hot metal nut test)	Low radius of char
BS5808 Static loading BS4939 Method:	Thickness loss after 24 hours loading and 24 hours recovery: Loss after 24 hours 30.8% (indicative)
Dynamic loading BS4052 method (indicative):	Loss after 1000 impacts 21.5%
Work of compression BS4098 method:	Retained thickness 65.6% (indicative)
Tog rating (indicative)	3.2
Sound insulation performance: (ISO 140-8)	30db sound impact reduction

This information is correct at time of press and is subject to the most recent product analysis. All data shown as mean values. The above data is given for information only and does not constitute a guide to the use of our products.



Anglo Technical Textiles
Tong Lane Whitworth
Lancashire, OL12 8BG
Tel: 0845 835 0210
Email: info@anglotechnicaltextiles.co.uk
Web: anglotechnicaltextiles.com