

Technical Data Sheet



Product name : Bondtred

Description : Carpet Underlay



Lightweight: Bondtred is an innovative, lightweight felt underlay. Designed for easy handling and to conform to increasingly strict health and safety requirements, each roll weighs just 8.25kg.

Resilient: Blend of wool and synthetic fibre gives excellent resistance to permanent compression.

Clean: A sealed surface locks in fibres to prevent dust and gives a clean, consistent appearance.

Warm: Wool content ensures retention of the best properties of a traditional felt, including high thermal insulation and resistance to permanent compression.

Green: Bondtred is manufactured entirely from recycled fibre giving you value for money and environmental peace of mind.

Fibre composition:	Wool/polypropylene
Nominal weight:	550g/m²
Nominal thickness:	6mm
Roll width:	1.5m
Roll length:	10m
Standard roll area:	15m²
Flame retardancy: BS4790:1987 (Hot metal nut test)	Achieves a 'high radius of effects of ignition'
BS5808 Static loading BS4939 Method:	Thickness loss after 24 hours loading and 24 hours recovery: 36.8%
Recommendation:	Bondtred conforms to BS5808 (1991). A copy of the WIRA independent test results is available on request. It is recommended for 'heavy contract' use.
Tog rating (indicative)	1.5

This information is correct at time of press and is subject to the most recent product analysis. All data shown as mean values. The above data is given for information only and does not constitute a guide to the use of our products.



Anglo Technical Textiles
Tong Lane Whitworth
Lancashire, OL12 8BG
Tel: 0845 835 0210
Email: info@anglotechnicaltextiles.co.uk
Web: anglotechnicaltextiles.com